

ADT SERIES



MOST POPULAR ADT

The K-Tec™ 1237 ADT is designed for self loading with a 40-ton, 400+ horsepower rock truck. The 1237 ADT offers more power to the ground with the functionality from an existing rock truck unit. It features fast hydraulics, a smooth ride, and joystick scraper control.

Phone: 1-204-746-6435 Toll Free: 1-866-496-7561



1237 ADT SPECIFICATIONS

General Specifications	Standard	Metric
Heaped Capacity (ISO)	37 Cubic Yards	28.28 Cubic Metres
Struck Capacity	20.25 Cubic Yards	15.5 Cubic Metres
Max Loading Rating	88,000 lbs	39,916 kgs
Bucket Dimensions	12' W x 4' 3" H x 12' 10" L	3.66m W x 1.29m H x 3.91m L
Cutting Width	14'	4.27m
Cutting Edge	3-Piece Blade	3-Piece Blade
Gate Opening	80"	2.03m
Rack Height (Tiltable)	4'	1.21m
Gate Cylinders	5" x 26"	127mm x 711mm
Lift Cylinders	5.5" x 32"	140mm x 813mm
Ejector Cylinder	5.5" x 76"	140mm x 1,930mm
Transport Cutting Edge Clearance	28"	0.71m
Ball To Rear Axle Length	28' 9"	8.77m
Turning Radius	30'	9.14m
Wrap Around Mud Scrapers	Standard	Standard
Gate Extension	Standard	Standard
Radial Tires (4)	26.5 R25	26.5 R25


























Optional Upgrades	
Height Gauge	Increases cutting depth visibility
Brake System	4 caliper disc brakes
Skid Shoe System	Provides superior stabilization for precision finish cut
Truck Fender System	Protects truck from material flinging from tires
Truck Chassis Catwalk Sytem	Easy access steps and platform
Mine Version	Heavier plate steel for mining applications

Recommended Power Units

Articulated Dump Truck 400HP +/298 KW +



Transportation Measures	Standard	Metric		
Overall Width	 - 14'	 4.27m	-	
Overall Height	10'	3.04m		
Overall Length = = = = = =	-36' 6"	- 11.13m		
Shipping Weight	39,130 lbs	17,749 kgs		
"Specifications are subject to change without notice"				

⊞ Gallery

Topsoil, Texas USA



Topsoil / Virginia, USA



Topsoil / Montana, USA



Sand + Clay / Colorado, USA



Topsoil / Queensland, Australia



Clay / Texas, USA



Sand + Topsoil / North Dakota, USA



Phone: 1-204-746-6435 Toll Free: 1-866-496-7561